

# M5 Diagnostic Ultrasound System

# Datasheet



SHENZHEN MINDRAY  
BIO-MEDICAL ELECTRONICS CO., LTD.

## General information

### Dimensions and weight

- Height: 75 mm (2.95 inch)
- Width: 361 mm (14.21 inch)
- Depth: 357 mm (14.06 inch) with handle
- Weight (main unit, without battery): less than 6 kg (13.23 lb.)

### Electrical power

- AC adapter input
  - Voltage: 100VAC~240VAC
  - Frequency: 50/60 Hz
  - Input current: 2A (maximum)
- AC adapter output
  - Voltage: 12VDC
  - Output current: 10A (maximum)
- Battery
  - Exchangeable li-ion batteries: 11.1VDC, 4500mAh
  - Continuous scanning for more than 1h (normal condition)

## User interface

### Operator keyboard

- Soft keys for fast and intuitive control
- Alphanumeric keyboard
- 8-segment TGC, with remapping functionality at any depth
- Interactive backlit keys
- User-centric control panel with home based design
- Blank keys for user-define functions
- User-define lay out of soft keys and menu items

### Display screen

- High-resolution color LCD
  - Diagonal dimension: 15 inch
  - Resolution: 1024X768
  - Brightness adjustment
- Integrated speakers
  - Volume adjustment

### Intelligent workflow

- Synchronous navigation: On-screen instructions for manual-free operations

- System hibernation: Switch off transducer emission and launch screensaver
- Context-based soft keys: Easy access to system menus and active parameter adjustment
- Q-click™: click and adjust on-screen parameters directly
- Thumbnail: easy review during live scanning
- Editable report and print preview

## **System overview**

### **Application**

- Abdomen
- Cardiology
- Gynecology
- Obstetrics
- Urology
- Small Part
- Pediatrics
- Musculoskeletal
- Orthopaedics
- Intraoperative
- Peripheral Vascular
- Transcranial Doppler
- FAST (Focused Abdominal Sonography For Trauma)
- Nerve and tendon

### **Scanning method**

- Electronic convex
- Electronic linear with slant scanning
- Electronic sector

### **Transducer types**

- Convex array
- Microconvex array
- Linear array
- Phased array

### **Imaging modes**

- B mode
- M mode
- CDFI (Color Doppler Flow Imaging, Color)

- Power (Power Doppler Flow Imaging, including DirPower, directional power Doppler)
- Pulse Wave Doppler (PW)
- Continuous Wave Doppler (CW, optional)

### **Special imaging features**

- Tissue harmonic imaging
- Slant scanning for linear transducers (B, color/power, PW independent)
- Trapezoid imaging for linear transducers
- iBeam™ spatial compounding imaging for linear probes
- HPRF for PW
- Multi-frequency in both 2D and Doppler imaging

### **Display mode**

- Quad/dual display (for B, color and power modes)
- B/C Live (B and color simultaneous comparison display)
- Duplex for simultaneous B and PW/CW
- Triplex mode for simultaneous B, color/power, and PW/CW
- Time line display: left/right and top/bottom (1:1, 1:2, full)

### **Standard configuration**

- High resolution 15 inch LCD display
- Pulse Wave Doppler
- HPRF
- Color Doppler Flow Imaging
- Power Doppler Flow Imaging
- Directional Power Doppler Flow Imaging
- Tissue Harmonic Imaging
- Trapezoidal Imaging
- iBeam™
- iTouch™
- 80G integrated hard disk
- iStation™
- USB ports
- Ethernet port
- S-video out port and cable
- Measurement & calculation software packages
- Multi-language screen display
- Convex array transducer 3C5s (2.5/3.5/5.0/H5.0/H6.0MHz)
- Trolley case

### **Software options**

- DICOM 3.0 software
- iScape™ View (Panoramic imaging)
- Smart3D™ (Freehand 3D)

### **Hardware options**

- Additional transducer connectors
- CW
- Transducers
- Needle guide brackets
- I/O module for data transportation
- USB V/A module for VCR connection
- USB ECG module with electrodes and cables (AHA/IEC)
- External USB DVD-R/W
- Spare battery
- Foot switch with programmable functionality
- Trolley

### **Peripherals**

- Thermal B/W video printer
- Thermal color video printer
- Digital video B/W or color printer
- USB text/graph printer
- VCR
- DVD recorder

## **Imaging processing and presentation**

### **System architecture**

- Powerful Multi-beam Parallel Imaging (MBP)
- Fine Tissue Optimization (FTO)
- Transmitting Spectrum Focusing (TSF)
- Innovative Transmitting Apodization (ITA)
- Accurate Vessel Imaging (AVI)

### **Intelligent imaging processing**

- iTouch™: intelligent one touch optimization for both 2D and PW images
- IP(image processing): one grouped parameter for B and color image fast optimization

## **Imaging platform**

- All-digital broadband beam-former
- 1024 digital processing channel technology
- Displayed depth
  - Minimum: 26 mm, transducer dependent
  - Maximum: 308mm, transducer dependent
- Focus
  - 1~4 focus points selectable (depth dependent)
  - Up to 8 focal positions selectable (depth dependent)
- Wideband processing technology
  - Fundamental frequencies: 3 steps
  - Harmonic frequencies: 2 steps
  - Doppler frequencies: 2 steps
- Gray scale: 256 levels
- Total system dynamic range: 160 dB
- Zoom
  - RAZ (regional acoustic zoom)\* and pan zoom
  - PIP (picture in picture)
  - Zoom ratio: up to 1000%
  - For real-time or frozen images

## **B mode**

- Acoustic power (10~100%, 6% step)
- Gain (0~100dB)
- TGC (8 segments, with re-mapping functionality at any depth)
- Frame Rate (up to 396f/s, transducer dependent)
- Focus number (1~4)
- Focus position (8 steps)
- FOV (N, M1, M2, W)
- Line density (L, H)
- Steer (-12°, 0, 12°)
- TSI (Tissue, Muscle, Fat, Fluid) *tissue specific imaging*
- Display dynamic range (30~100dB)
- Frame average (0~7)
- Noise rejection (0~3)
- Edge enhancement (off, 1~4)
- IP (1~8) *image processing*
- Colorize (7 maps)
- Gray map (1~8)
- Gray Transform
- Gray Rejection
- $\gamma$  correction (0~3)

- Rotate (0°, 90°, 180°, 270°)
- Flip (left/right, up/down)

### **M mode**

- Display mode: scroll
- Sweep speed (1, 2, 4, 8 s/screen)
- Gain (0~100dB)
- Display dynamic range (30~100dB)
- MIP (1~8)
- M soften (0~4)
- Gray map (1~8)
- Colorize (7 maps)
- Time mark (on, off)
- Display format (L/R, V1:1, V1;2, Full)

### **Color mode**

- Gain (0~100dB)
- Frequency (2 frequencies)
- Frame Rate (up to 448f/s, transducer dependent)
- Steer (-12°, 0°, 12°)
- PRF (1.3kHz~14.5kHz)
- Scale ( $\pm 2.3\text{cm/s}$ ~ $\pm 246\text{cm/s}$ , up to 492cm/s in one direction, transducer dependent)
- Color IP (1~8)
- Baseline (17 levels)
- Color map (1~11)
- Wall filter (0~7)
- Line density (L, H)
- Packet size (0-3)
- Flow state(L, M, H)
- Smooth (0~4)
- Persistence (0~4)
- Contrast (0~3)
- Priority (0~100%, 10% step)
- Map invert (on, off)
- Focus position (10 levels)
- B/C wide (on, off) *automatically adjust the 2D image size according to the color ROI*
- ROI color (off, red, green, blue, cyan, MAG, yellow, white)
- B/C dual live (on, off)
- Image display (on, off)

### **PW/CW mode**

CW mode is available only with phased array transducers.

- PW frequency (2 frequencies)
- PRF (1.3kHz~11.4kHz)
- PW Scale ( $\pm 6.1\text{cm/s} \sim \pm 291.7\text{cm/s}$ , up to 583.4cm/s in one direction, transducer dependent)
- CW Scale ( $\pm 0.61\text{m/s} \sim \pm 15.04\text{m/s}$ , up to 30.08m/s in one direction, transducer dependent)
- Dynamic range (24~72dB)
- Baseline (9 levels)
- Sweep speed (1, 2, 4, 8s/screen)
- Sample volume (0.5~15.0mm)
- Sample depth (up to 308mm)
- Steer ( $-12^\circ, 0^\circ, 12^\circ$ )
- Angle correlation ( $-80^\circ \sim 80^\circ$ )
- Colorize (7 maps)
- Wall filter (7 levels, scale dependent)
- Auto Trace and auto calculation (PS, ED, MD, TAMAX, PPG, MPG, VTI, PI, RI, S/D, D/S, AT, DT, HR, PV)
- Duplex (on, off)
- Triplex (on, off)
- Trace Area (Below, Above, All)
- Trace smooth (off, 1~4)
- Trace sensitivity (0~5)
- Audio (on, off)
- Full screen (on, off)
- Time mark (on, off)
- Display format (L/R, V1:1, V1:2, Full)
- HPRF (on, off)

### **Power/DirPower mode**

- Display dynamic range (10~70dB)
- Power IP (1~8)
- Power Map (1~8)
- Line density (L, H)
- Flow state (L, M, H)
- Packet size (0~3)
- Wall filter (8 levels)
- Smooth (0~4)
- Persistence (0~4)
- Contrast (0~3)
- Priority (0~100%, 10% step)

- Invert (on, off)
- B/C wide (on, off) *automatically adjust the 2D image size according to the ROI*
- LVR (Low velocity resistance) (off, 1~7)
- Focus position (10 levels)
- ROI color (off, red, green, blue, cyan, MAG, yellow, white)
- B/C live (on, off)
- Dual live (on, off)
- Image display (on, off)

### **iScape™ View (optional)**

- iScape™ view is also called panoramic imaging.
- Available on all convex and linear array transducers
- Based on real-time imaging of 2D mode (not available in Color or Power mode)
- Displays up to 40cm in length (frame rate and scanning speed dependent)
- Rotate (0~360°, 5° /step)
- Zoom (10%~200%, actual size, fit size)
- Colorize (7 maps)
- Store and review image capture process
- Store and review iScape™ images
- Post processing on stored images
- All 2D measurement items available, except depth, profile and histogram

### **Smart3D™ (optional)**

- Smart3D™ is also called freehand 3D.
- Available on all convex, linear and phased array transducers without sensor
- Method (linear, fan)
- Distance (10~200mm)
- Angle (10°~80°)
- Render (surface, max, min, X-ray)
- Smooth (0~5)
- Gamma bias (0~100%)
- Gamma position (0~100%)
- Colorize (7 maps)
- Rotate (X, Y, Z axis)
- Store and review Smart3D™ images
- Cut (C.inside, C.outside, R.inside, R.outside)
- Adjust VOI (on, off)

### **ECG**

- Gain
- Position
- Trigger mode (single, dual, AT, timer)

- HR display

### **Cineloop**

- Support 2D, M, PW, Color, Power, DirPower
- Simultaneous and independent review in duplex/triplex mode
- ECG wave for retrospective review
- Capacity:
  - 2D, Color, Power, DirPower: Maximum >1200 frames
  - M, Spectral Doppler: Over 131s
- Variable cine playback speed
- User-define start and end frame of cine storage
- Permanent storage in hard disk and display in real-time and duplex modes
- iVision: Automatic slides show

### **iStation™**

Intelligent patient information management platform

- Quick image and cine storage
- Auto image review: automatic browser, icon review
- Offline analysis system
- Professional clinical reports with images embedded
- Integrated search engine for patient information
- Intelligent data backup
- Support DICOM worklist from server and file transfer in DICOM format on internet (optional)

### **Storage**

- 80 GB integrated hard drive
- External DVD-R/W (optional)
- USB ports
- Still images storage format: BMP, JPG, DCM and FRM (defined by Mindray, support offline analysis function)
- Cine loops storage format: AVI, DCM and CIN (defined by Mindray, support offline analysis function)

## **Measurement and calculation**

- Software packages for various specific clinical use
- Comprehensive analysis methods
- Clinical analysis reports

## **General Measurement package**

### **General B mode measurement**

- Depth
- Distance
- Angle
- Area
- Volume
- Cross Line
- Parallel Line
- Trace Length
- Ratio
- B Profile
- B Histogram

### **General M mode measurement**

- Distance
- Time
- Slope
- Heart Rate
- General Color mode measurement
- Color velocity

### **General PW/CW mode measurement**

- Velocity
- Acceleration
- Resistance index
- Spectrum trace
- Heart rate

## **Clinical Analysis Packages**

### **Obstetrics**

- Fetal measurement
- Fetal weight calculation
- Calculation items, such as HC/AC, FL/AC, FL/BPD, AXT
- Amniotic fluid index
- Fetal biophysical profile
- Fetus Doppler measurement
- Multi-fetus exam
- Estimated delivery date display
- Growth Curve: Four curves display for comparison

(GA calculation formulas include but may not be limited to the following: Tokyo, Hadlock, Jeanty, Hohler, Merz, Kurtz, Sabbagha, Hansmann, Rempen, Osaka, Chitty, O'Brien and Warda. EFW formulas include Hadlock1, Hadlock2, Hadlock3, Hadlock4, Shepard, Merz1, Merz2, Hansmann, Tokyo, Osaka and Campell.)

## **Cardiac**

- Left ventricular function measurement
  - Single Plane Ellipse method
  - Biplane Ellipse method
  - Bullet method
  - Simpson's method
  - Simpson's Single Plane Ellipse method
  - Simpson's Biplane Ellipse method
  - Cube method
  - Teichholz method
  - Gibson method

- Left ventricular
- Right ventricular
- Aortic
- Main pulmonary artery
- Mitral valve
- Tricuspid valve
- Pulmonary valve
- Pulmonary vein valve
- Volume flow
- Heart rate

(Cardiac calculation results include but may not be limited to the following items: HR, EDV, ESV, SV, CO, EF, CI, SI, LV Mass, LVMWI, FS, MVCF, ET, PHT, MV-Area, VTI, MPG, MV-IRT, MV-DcT, RVSP, AoV-Area, RV-ET, RV-AcT, RV-PEP, RV-AcT/ET, RV-STI, PV DcT, PV-SF and Volume Flow.)

## **Gynecology**

- Endometrium
- Uterus
- Uterine cervix
- Uterus/cervix
- Ovary
- Follicle

## **Small Parts**

- Thyroid

## **Urology**

- Prostate
- Left/right Seminal Vesicle
- Left/right Renal
- Left/right Adrenal
- Residual Volume
- Left/right Testicular

## **Orthopaedics**

- Hip angel: BL, IL, ARL, Angle between BL/ARL, Angle between BL/IL

## **Peripheral Vascular**

- Left/right Distal Common Carotid Artery
- Left/right Middle Common Carotid Artery
- Left/right Proximal Common Carotid Artery
- Left/right Distal Internal Carotid Artery
- Left/right Middle Internal Carotid Artery
- Left/right Proximal Internal Carotid Artery
- Left/right Distal External Carotid Artery
- Left/right Middle External Carotid Artery
- Left/right Proximal External Carotid Artery
- Left/right Distal Vertebral Artery
- Left/right Middle Vertebral Artery
- Left/right Proximal Vertebral Artery
- Left/right Distal Subclavian Artery
- Left/right Middle Subclavian Artery
- Left/right Proximal Subclavian Artery
- Left/right Distal Subclavian Vein
- Left/right Middle Subclavian Vein
- Left/right Proximal Subclavian Vein
- Left/right Bulbillate
- Innominate Artery
- Left/right Upper Extremity
- Left/right Lower Extremity
- Volume flow
- Stenosis

## **System setup**

### **User-define functions**

By user-define function, users could

- Customize twenty four user-define exam modes, including but not limited to

- Exam mode name
- Imaging parameters
- General measurement items for each imaging mode
- Measurement packages
- Obstetric formula
- Comment library
- Body mark library
- Layout of soft keys and menu items
- Create new measurement items, or new calculations based on measurement results
- Set volume calculating index
- Assign frequently used functions to user-define buttons on control panel and foot switch
- Adjust key volume, key lightness and trackball speed

### **Multi-language**

- Screen display, keyboard layout\* and user manuals\* support
- English
  - German
  - French
  - Spanish
  - Portuguese
  - Italian
  - Russian
  - Chinese

### **Operation system**

- Windows™ XP Embedded system  
Windows is a registered trade mark of Microsoft Corporation.

## **Transducers**

### **Sockets**

- One universal array transducer socket
- One dedicated CW Doppler pencil socket
- Optional three universal array transducer sockets (additional transducer connector)

### **Models**

- Convex array transducer 3C5s (2.5/3.5/5.0/T5.0/T6.0MHz)
- Linear array transducer 7L4s (5.0/7.5/10.0MHz)
- Linear array transducer 10L4s (8.0/10.0/12.0MHz)

- Linear array transducer 7L6s (5.0/7.5/10.0MHz)
- Biplanar transducer 6LB7s (5.0/6.5/8.0MHz)
- Convex array transducer 6CV1s (5.0/6.5/8.0MHz)
- Endorectal array transducer 6LE7s (5.0/6.5/8.0MHz)
- Convex array transducer 6C2s (5.0/6.5/8.0MHz)
- Phased array transducer 2P2s (2.0/2.5/3.0/H3.5/H4.0MHz)

## **Inputs and outputs**

### **Main unit**

- USB (2)
- Ethernet
- S-video out
- I/O module connector

### **I/O module**

- USB (2)
- Parallel port
- Serial port
- Composite video out
- Audio out (L/R)
- VGA out
- Microphone in

### **V/A module**

- S-video in
- Composite video in
- Audio in (L/R)

\*Not available yet.